



LAMBERET

REFRIGERATED ISOTHERMAL BODIES FOR VOLKSWAGEN UTILITY VEHICLES

NEW FRIGOLINE

3 body versions made for your business.

FRIGOLINE

attractive, lightweight, and ergonomic with ""Easy-Handles""

FRIGOLINE PRO

ultra-sturdy: reinforced stops, floor, and plinths, stainless steel triple OT frame

FRIGOLINE PRO BEEF

designed and optimised for transporting hanging meat

N°Vert 0 800 308 530

Transporter CHASSIS



Transporter **CHASSIS**





Cab-floor type lowered body with optional wheel arches







Reinforced rear protection (Pro pack)



I movement ""Easy Handle"

This body is intended for transport under controlled temperature, in compliance with the ATP regulations in force.







BASIC VEHICLE FOR CONVERSION

Transporter T6 single chassis cab.

Short or long wheelbase, 4x2 or 4Motion

Recommended options:

IS2 (electric and ECU interface) if refrigeration unit for Stop&Start compatibility. If vehicle more than 6 m overall: with LED side lights.

If direct drive unit:

2.0 TDI Euro 6; 84, 102, 150, 204 HP: without air conditioning; 4x4 compatible; DSG compatible. Stop&Start compatible if IS2.

LAMBERET BODY & INSULATION

NEW FRIGOLINE body, "Reinforced Insulation" quality, made up of panels with increased thickness 85 mm in antibacterial-polyester-polyurethane gel-coat, fitted with aluminium inserts. Design according to HACCP specifications.

4 int. heights (1.80/1.95/2.05/2.15 m), 2 usable widths (1.82/1.91) and 5 rear openings (OB1 - OB2 - OT2 - OT3 - OR) available.

Standard: total 2-leaf rear opening OT2 on reinforced bolted frame, "Easy-handle" 1 movement handle, aluminium mouldings, LED interior lighting, non-skid floor with 1 outflow front right and aluminium plinths on 3 faces, retractable rear step.

REFRIGERATION UNIT | CARRIER, THERMOKING, EDT, etc.

Positive or negative refrigeration unit, Class A or C, placed on front face. Power and technology (generator or direct drive) customised depending on use

Unit options: road/mains dual mode, unit cover paint, heating, temperature recorder, aerodynamic deflector.

CONFIGURATIONS | CATERING, DISTRIBUTION, MEAT, SEAFOOD, HEALTH, etc.

PRO PACK: Reinforced floor + HD aluminium plinths + reinforced sealing corner stays for front plinths + triple thickness VHTS steel/aluminium/stainless steel frame + full-length and height sill protection + 2 stops on vertical uprights + 2 flush rear clearance light stops if the vehicle is equipped with them as an option.

BEEF PACK: With insulated steel roof inserts every 610 mm, suitable for attaching hangers. Hanging meat transport solution up to 3.5 T GVWR.

PRO BEEF PACK: Combination of "PRO" and "BEEF" packs up to 7.5 T GVWR.

"Distribution" low floor with wheel housings.

1 (OB1) or 2 (OB2) leaf swing rear access, integrated door locks. Total 3-leaf rear opening (OT3) on reinforced bolted frame, 1.91 and 2.06 wide. Side swing (900xhi) or sliding (900x1930) door. Partition, adjustable, height-adjustable shelves, rails, beams, Interinox, meat hangers (on BEEF), seafood sill, tailgate.

Example DIMENSIONS en mm: other dimensions available, consult us	Short wheelbase 3000	Long wheelbase 3400
Body length	2650	3050
Overall length	5254	5654
Overall width	1995/2090	1995/2090
Overall height	2705	2705
Usable length	2480	2880
Usable width	1820/1910	1820/1910
Usable height	1800	1800
Extension/recess	100/50	100/50
Sill height	820	820
Volume (m³)	8.1/8.5	9.4/10
Insulation weight (kg, example, excluding unit and options)	460/480	530/550



You Tube







Data according to version. Non-contractual document. Pictures may show optional equipment. As part of its continual improvement policy, LAMBERET reserves the right to modify the characteristics of conversions without prior notice. Photo predict LAMBERET SAS. — 04/2018



