



LAMBERET

REFRIGERATED ISOTHERMAL BODIES FOR
VOLKSWAGEN UTILITY VEHICLES

Crafter
CHASSIS

NEW **FRIGOLINE**

3 body versions made for your business.

FRIGOLINE

attractive, lightweight, and ergonomic
with "Easy-Handles"

FRIGOLINE PRO

super-sturdy: Reinforced stops, floor, and
scuff plates, stainless steel triple OT
frame

FRIGOLINE PRO BEEF

designed and optimized for transporting
hanging meat

N° Vert 0 800 308 530

APPEL GRATUIT DEPUIS UN POSTE FIXE EN FRANCE

 **LAMBERET**
Le maillon fort de la chaîne du froid

www.lamberet.com

Crafter

CHASSIS



This body is intended to transport goods at controlled temperatures, in accordance with current ATP regulations.



BASIC VEHICLE FOR CONVERSION

Single-cab Crafter body.

Recommended options:

- Stronger suspensions/shock absorbers and heightened stabilization (2MG, if laden).
- Rear lights with longer cables (cable 1.5m longer) (8SE).
- Preparation for the 3rd stop light, raised (8R6).
- If tailgate: Preparation for electric tailgate (5S4), delivery preparation pack (ZVB).

If refrigeration unit:

Example data - Ask us first to verify compatibility, time needed, and the unit's size.

No Stop&Start, or can be disabled with bodymaker's preparation of choice (IS2): Electric terminal board and function control device 1 with ABH programming.

- TRACTION 2.0 TDI 102 RS | 140 RS | 177 RS: Available with air conditioning (ZK1 or ZK2).
- TRACTION 2.0 TDI 102 RS | 140 RS: Pulsor available with air conditioning; prohibited on 8HI.
- PROPULSION 2.0 TDI 122 RJ | 140 RS | 177 RS/RJ: Ask us for unit kit availability.
- 4MOTION 2.0 TDI 140 RS | 177 RS: Ask us for direct-drive unit kit availability.
- 4MOTION 2.0 TDI 140 RS: Pulsor available with air conditioning; prohibited on 8HI.

LAMBERET BODY & INSULATION

NEW FRIGOLINE body ATP-quality Heightened Insulation, sealed system of 85mm-thicker **composite panels, designed and manufactured by Lamberet**. Polyurethane core with very high insulating power, hydrophobic treatment. Internal and external walls made of non-deforming polyester coated with antibacterial gel-coat. Built-in aluminum moulding with aerodynamic front CX profiles.

5 int. heights (1.80 | 1.95 | 2.05 | 2.15 | 2.25m), 3 usable widths (1.82 | 1.91 | 2.06m) and 5 rear openings (OB1 | OB2 | OT2 | OT3 | OR) available.

Standard: Rear full-width two-leaf OT2 opening on bolt reinforced frame; single-motion Easy Handles, EDL-assisted rotating door stop, LED interior lighting, skid-proof floor with one front right channel and aluminum scuff plate on three sides, retractable rear step, side lights (on vehicles longer than 6 m).

REFRIGERATION UNIT | CARRIER, THERMOKING, EDT, etc.

Refrigeration unit classified as A/POSITIVE or C/NEGATIVE, placed on front side.

Power and technology (generator or direct-drive) customized depending on how used.

Unit options: Dual-mode highway/local, unit cover paint, heating, temperature recorder, door-activated switch, aerodynamic deflector, multi-temperature, Pharma certification

FEATURES | CATERING, DISTRIBUTION, MEAT, SEAFOOD, MEDICAL, etc.

PRO PACK: Reinforced floor + HD alum. scuff plates + reinforced sealing angle brackets on front scuff plates + triple-thick VHEL steel frame | aluminum | stainless steel + full-length and width threshold protection + 2 stops on vertical uprights + 2 sunken rear clearance light stops if the vehicle is equipped with them.

BEEF PACK: Insulated steel ceiling inserts every 610 mm, suitable for attaching hangers. Meat transport solution up to 3.5 T or 7.5 T (PRO) of GVWR.

OPTIONS:

1 (OB1) or 2 (OB2) swing-open backs, integrated door locks. Three-leaf open back (OB3) on bolted reinforced frame 1.91 and 2.06 wide. Swing-open (900xhi) or sliding (900x900) side door, partition, adjustable and liftable shelves, rails, runners, Interinox, hangers (on BEEF and PRO BEEF models), slanted threshold, tailgate, backup camera, advertising, etc.



Aluminum body version



Interinox + rails + hangers option



Reinforced rear protection (Pro pack)



Single-motion "Easy Handle"

Example dimensions (m)	Wheelbase 3640		Wheelbase 4490		Wheelbase 4490	
	Standard		Long		PAF Long	
Wheels	Single	Twin	Single	Twin	Single	Twin
Overall length	6.29		6.99		7.59	
Overall height	2.09	2.24	2.09	2.24	2.09	2.24
Overall usable height FWD RWD-AWD	2.90 3.00	- 3.02	2.90 3.00	- 3.02	- 3.00	- 3.02
Usable length	3.18		3.88		4.48	
Max usable width	1.91	2.06	1.91	2.06	1.91	2.06
Usable height besides evaporator	1.95	2.15	1.95	2.15	1.95	2.15
Loading threshold FWD RWD-AWD	0.86 0.96	- 0.98	0.86 0.96	- 0.98	- 0.96	- 0.98
Usable volume (m ³)	11.8 to 14.1 m ³		14.5 to 17.2 m ³		16.7 to 19.8 m ³	
Mass (kg) besides options and unit	641	693	760	821	862	931

* Data differs by version. Document not binding. Pictures may show optional features. As part of its continual improvement policy, LAMBERET reserves the right to modify the characteristics of conversions without prior notice. Photo credit: LAMBERET SAS - 012018



YouTube



f



in



www.lamberet.com

LAMBERET SAS | #1 in refrigerated utility and industrial vehicles in Europe.

129 route de Vonnas - BP 43 - 01380 Saint-Cyr/Menthon - France | +33 (0)3 85 30 85 30 | communication@lamberet.fr